

# "SLASHBUSTER"®

## HD 482 & HD 422

### Excavator Mounted Brush Cutting Attachment

**MAGNUM**  
**STANDARD DRIVE SYSTEM**

**Recommended for  
Long Front or  
Standard Front  
Excavators**

**"SLASHBUSTER"  
State-of-the-Art  
Land Management and  
Right-of-Way Equipment**

*It's Not How Fast You Cut,  
It's How Well You Cut Fast*

*Exclusive Worldwide Patents  
The Most Versatile Cutter Available*

Applications of the D&M "SLASHBUSTER"® Equipment

1. Building roads over swampy ground
2. Clearing and grubbing contracts
3. Clearing building sites
4. Eliminates slash disposal burning in populated areas
5. Cuts costs of trucking debris from cleared areas.  
All cuttings are mulched into soil.
6. Builds new and maintains established right-of-ways.
7. Retards tall growing trees eliminating blanket spray programs
8. Daylighting roads cutting the expense of sanding
9. Sight obstructions removed from corners and intersections.
10. Better maintenance of drainage ditches.
11. Brush clearing around bridges gives greater exposure to sunlight with easier and more economical maintenance, especially with older structures.



Mulching Teeth in Shroud



# "SLASHBUSTER"®

## HD 482 & HD 422

### Excavator Mounted Brush Cutting Attachment

#### HD 482

##### General Specifications

- 52" cutting swath
- Cuts and mulches trees to 18" diameter
- Adaptable to 40,000 to 100,000-lb excavators
- Adjustable 350 to 550 RPM wheel speed
- 2,900-lb. total weight\*

#### HD 422

##### General Specifications

- 46" cutting swath
- Cuts and mulches trees to 14" diameter
- Adaptable to 24,000 to 60,000-lb excavators
- Adjustable 350 to 550 RPM wheel speed
- 2,500-lb. total weight\*

#### Basic Installation Requirements for Both Models

##### Hydraulic:

- Continuous service priority flow circuit required
- 32 GPM to 44 GPM\*
- 4,000 PSI maximum hydraulic pressure
- Three position directional control valve recommended
- "SLASHBUSTER"® attachments are provided with integral crossport relief and anti-cavitation check valves

##### Electric:

- 20 AMP auxiliary circuit recommended
- Foot-operated master On-Off switch recommended
- Cab mounted control for forward, neutral and reverse with indicator lights recommended

\*Varies with excavator size and options

**Note:** It is recommended that the excavator is provided with a hinged front screen guard for the front of the cab that meets or exceeds SAE J1084 specs.

#### HD 482 & HD 422 Standard Features:

- MAGNUM drive system
- Automatic wire shear
- Rotating hub debris guard
- Cutting disk with S-7 cast and hardened teeth
- Mulching teeth in shroud

#### HD 482 & HD 422 Options:

- Available to operate with standard bucket thumb
- Available to match any bucket quick disconnect
- "VCP" remote spot herbicide applicator
- Ninety-degree tilt mount
- Hydraulic trim saw



## "SLASHBUSTER"®

### EQUIPMENT

Unmatched in Performance,  
Reliability and Output



D&M Machine Division, Inc.

12 Monte-Brady Road Montesano, WA 98563  
(360) 249-3366

email: [info@slashbuster.com](mailto:info@slashbuster.com)  
[www.slashbuster.com](http://www.slashbuster.com)

Exclusive Manufacturer of "SLASHBUSTER"® Equipment

THIS EQUIPMENT IS PROTECTED BY ONE OR MORE OF THE FOLLOWING PATENTS: 4,769,977; 5,103,882; 5,201,350; 5,329,752; 5,408,814; S/N 08/720,536; AUSTRALIAN PATENTS: 600716; 618679; 652131; 654411; 665724; CANADIAN PATENTS: 1,281,908; 2,084,971; NEW ZEALAND PATENTS: 245249; 270419; EUROPEAN PATENT 0298977, REGISTERED IN GB, FR, IT, CH, NL, BE (298977E), DE (37793098), AT (0076250E), SE (879019487); AND PATENTS PENDING IN THE UNITED STATES, AUSTRALIA, CANADA, EUROPE, FINLAND AND NEW ZEALAND.