

"SLASHBUSTER"[®]

XL 460

Brush Cutting Attachment for Small Excavators

XL 460

General Specifications

- Adaptable to 6-8 ton excavators
- Cuts and mulches brush to 3" diameter
- 46 inch cutting swath with flail blade
- 750-800 pounds total weight
- Automatic wire shear standard
- Rotating hub debris guard standard

Options:

- 90 degree tilt mount
- Remote herbicide applicator
- Integration with bucket quick disconnects
- Integration with standard excavator bucket thumb



Triple welded construction

Basic Installation Requirements

Motor Circuit:

- Excavator auxiliary circuit
- 15 GPM to 32 GPM flow
- 2,500 PSI minimum recommended
- "SLASHBUSTER"[®] attachments are provided with crossport relief and anti-cavitation protection

Recommended Electric:

As needed

Note: It is recommended that the excavator is provided with a hinged front screen guard for the front of the cab that meets or exceeds SAE J1084 specs.



Flail blade cutter
46" cutting swath

"SLASHBUSTER"[®]

Land Management Equipment
Unmatched in Performance,
Reliability and Output



D&M Machine Division, Inc.

12 Monte-Brady Road Montesano, WA 98563
(360) 249-3366

email: info@slashbuster.com
www.slashbuster.com

Exclusive Manufacturer of "SLASHBUSTER"[®] Equipment

Part of a line of brush cutter attachments to fit
2,000-100,000 lb. excavators.

Download videos, brochures at Slashbuster.com

THIS EQUIPMENT IS PROTECTED BY ONE OR MORE OF THE FOLLOWING PATENTS: 4,769,977; 5,103,882; 5,201,350; 5,329,752; 5,408,814; S/N 08/720,536; AUSTRALIAN PATENTS: 600716; 618679; 652131; 654411; 665724; CANADIAN PATENTS: 1,281,908; 2,084,971; NEW ZEALAND PATENTS: 245249; 270419; EUROPEAN PATENT 0298977, REGISTERED IN GB, FR, IT, CH, NL, BE (298977E), DE (37793098), AT (0076250E), SE (879019487); AND PATENTS PENDING IN THE UNITED STATES, AUSTRALIA, CANADA, EUROPE, FINLAND AND NEW ZEALAND.